

Copyright c. 2010. Tutti i diritti sulle immagini ed i testi sono riservati. Sono vietate la riproduzione e diffusione, in qualsiasi forma, delle fotografie e dei testi. I trasgressori saranno perseguiti a norma di legge. Tutti i prodotti illustrati costituiscono creazione di proprietà della società Gruppo Piazzetta SpA. Ogni diritto di sfruttamento dei modelli è riservato. Il marchio ed i segni distintivi della società sono di proprietà esclusiva della stessa.



CP 32 ACS

Thermo Pellet boiler with structure, boiler, firebox, brazier and conveyor in steel. Heat exchanger cleaning system with rotating elements. Standard expansion tank, high-efficiency circulator. Reversible insulated steel exterior door, can be opened with handle.

COLOURS



Основная техническая информация

Технические данные

Firebox heat output	kW	34,9
Heat output to the water	kW	9,5 - 31,7
Thermal efficiency	%	89 - 90,9
Consumption at rated heat output	kg/h	2,2 - 7,1
Power supply	V-Hz	230 - 50
Electric power consumption	W	138 - 446
Standard flue outlet	cm	10
Hopper capacity	kg	70
Hopper capacity	l	35
Maximum operating pressure		1/2"
Mandata Ritorno		3/4"
Maximum operating pressure	bar	1,5
Weight stove	kg	265
Dimensions L x P x H	cm	70x64x139

Calculated based on nominal heat output and refers to rooms with a thermal requirement between 0.060 and 0.035 kW per m².

Доступность продукции может отличаться для каждой страны