P189 TH ACS

Thermo Pellet stove, cladded in Majolica in the following colours: Bianco Grigio, Bordeaux, Nero Opaco, Grigio Cerato, Rosso Lava and Terra Oriente. Rolling top system for easy loading. An original solution which stands out discreetly, becoming a valid choice for heating the domestic heating circuit.



GENERAL FEATURES

- ·Heating: hot water production forced ventilation
- ·Cladding: coated steel •Top: steel - majolica
- ·One-piece firebox: steel
- ·Boiler: steel
- •Firebox: steel Aluker®
- ·Fume deflector: steel
- Deflector: steel
- Exchanger cleaning: rotary cleaner system
- Brazier: steel
- ·Expansion tank: as standard feature
- ·Standard circulator pump: high efficiency
- ·Safety valve and relief valve: as standard feature •Door: cast iron with ceramic glass resistant to 750°C
- ·Handle: steel with nickel-plated finish
- Optional flue outlet: LH side
- •Standard flue outlet position: LH rear
- •Function control: panel with display and digital controls
- •Power adjustment: automatic with 16 levels depending on the set temperature
- •Timer-controlled thermostat with programming: 6 daily time frames
- Glass cleaning: continuous air flow
- Cyclic brazier cleaning: yes
- Energy Saving: yes
- Eco Function: yes
- Frost Function: yes
- ·Probe for managing storage tank: as standard feature
- •Probe for managing DHW storage tank: as standard feature
- •Can be connected to an external thermostat: yes
- ·AUX control: yes
- *Ash vacuum cleaner: as standard feature
 *Flue gas chamber ash pan: removable
 *Ventilation: optional

- •Electronically-controlled anti-condensation valve: optional
- ·Management via SMS: optional
- ·Installation: wall corner
- ·Flush with the wall installation: yes
- Combustion air kit: optional

TECHNICAL DETAILS

- Energy efficiency class A+
- •Rated thermal power (min max) kW 7,6 25,7
- *Rated thermal power (min max) kw 7,6 25
 *Thermal efficiency (min max) % 95,7 95,0
 *Max operating pressure bar 1.5
 *3-bar safety discharge valve Ø 1/2"
 *Heat system delivery Ø 3/4"
 *Heat system return Ø 3/4"
 *Pated consumption (min max) kg/h 1.6 5.6

- •Rated consumption (min max) kg/h 1,6 5,6
- Weight kg 275
- ·Standard flue outlet Ø cm 10
- Absorbed power (min max) W 75 405
- •Model P189 TH ACS

COVERS









